

SPX532.2

LITHIUM BATTERY



Lifting capacity

3200 kg



Max tip height

17,0 m



Dimensions (l x w x h)

3140 x 770 x 1990 mm




Powered by

Lithium battery



Weight

2750 kg



EN [m - kg]



FEATURES



INTUITIVE USER INTERFACE

Radio control

- Optimized usability
- Improved layout

Touch display

- 7" IP66 heavy duty
- Live load-chart and stability area
- Crane assistant onboard
- Self-diagnostics & troubleshooting

LITHIUM BATTERY POWERED

- Indoor operation, emission free
- Maintenance free
- Runtime over 1 workday
- On board 110/230V fast charger: 0-80% in 3 h (110V: 4:30 h)
- Adjustable charging current
- Work while charging



ENDLESS CRANE CONFIGURATIONS

- Hook** - Fast hook/winch switch
- Winch**: 80 m rope
- 800 kg capacity single fall / 3200 kg 4 falls
- Hydraulic jib** - 1000 kg SWL
- Hook or winch
- +16/-80° angle, up to 5,1 m length
- Unique self-installation system
- Tools**: Plug&Play connection



PICK & CARRY

- Up to 400 kg lifting capacity
- 360° turrett rotation
- Extendable crawler for improved driving



ACCURATE LOAD HANDLING

- Dynamic load sway control
- Automatic speed adjustment to ensure smooth and precise manoeuvres
- Automatic movement limitation to maximise safety
- Components engineered to maximise stiffness and load stability



SAFETY SYSTEMS

- Full LMI system
- Anti crash system
- Feedback on display



J-LINK POWERED BY TRACKUNIT*

- Remote fleet monitoring and diagnostics
- Built-in or retrofit on existing units







HIGH LIFTING CAPACITY IN REDUCED STABILITY


- Optimal lifting capacity/footprint ratio
- Optimized weight distribution

SINGLE DOORWAY

- Precise and easy to drive
- Non-marking white tracks for indoor*



DIMENSIONS



	MIN	
	$X_{\min}$	$Y_{\min}$
0°	620	5150
11°	1500	5060
23°	2330	4800
35°	3100	4360
47°	3760	3780
57°	4260	3140
68°	4620	2450
79°	4840	1650
90°	4920	850



	MAX	
	$X_{\max}$	$Y_{\max}$
0°	620	6250
11°	1720	6140
23°	2770	5800
35°	3730	5260
47°	4570	4530
57°	5190	3730
68°	5640	2830
79°	5930	1860
90°	6020	850

COMPACT FOOTPRINT

- 9 outriggers steps 0°/90°, independent configuration
- 2 outrigger extensions
- Self-levelling



LOAD CHARTS



TOOLS AVAILABLE

HYDRAULIC JIB

WLL 1000 kg



SEARCHER HOOK

WLL 1200 kg



BEAM/PIPE MANIPULATOR

WLL 500 kg - JIB500GR



GLASS MANIPULATOR

WLL 800 kg - JVM800R



SPX532.2
LITHIUM BATTERY

Jekko s.r.l. • info@jekko.it • www.jekko-cranes.com

Specifications are subject to change without notice.

All data provided is for reference purposes only and is not legally binding.